

SQP4N90C/SQPF4N90C

900V 4A N-channel Enhancement Mode Power MOSFET

Features

- Lower on-Resistance: $R_{DS(on)}=2.3\Omega$
- Good Stability and Uniformity with High E_{AS}
- 100% Avalanche Test
- Special Process Technology for High ESD Capability




Description

The SQP/PF4N90C is an high blocking voltage N-Channel power MOSFET. This device provide excellent performance for high voltage power supplies or pulse circuits.

Applications

- High Voltage Power Supplies
- Capacitor Discharge Applications
- Pulse Circuits

Package Type & Internal Circuit



Absolute Maximum Ratings @ $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	SQP4N90C	SQPF4N90C	Unit
V_{DSS}	Drain to Source Voltage	900		V
V_{GSS}	Gate to Source Voltage	± 30		V
I_D	Drain Current	$T_C=25^\circ\text{C}$	4	A
		$T_C=100^\circ\text{C}$	2.5	A
I_{DM}	Pulsed Drain Current (Note1)	19		A
P_D	Maximum Power Dissipation	$T_C=25^\circ\text{C}$	145	W
	Derate above 25°C	1.12	0.40	W/ $^\circ\text{C}$
E_{AS}	Single Pulsed Avalanche Energy (Note 2)	550		mJ
T_J	Operating Junction Temperature Range	-50~+150		$^\circ\text{C}$
T_{STG}	Storage Temperature Range	-50~+150		$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	SQP4N90C	SQPF4N90C	Unit
$R_{th(J-C)}$	Thermal Resistance, Junction to case	0.88	2.68	$^\circ\text{C}/\text{W}$
$R_{th(J-A)}$	Thermal Resistance, Junction to Ambient	62.5	62.5	$^\circ\text{C}/\text{W}$

Electrical Characteristics @T_C=25 °C unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV _{DSS}	Drain to Source Breakdown Voltage	V _{GS} =0V, I _D =1mA	900	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250uA	3.0	4.0	5.0	V
R _{DS(on)}	Static Drain-Source On-Resistance	V _{GS} =10V, I _D =2A	-	2.3	2.8	Ω
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =V _{DSS} , V _{GS} =0V	-	-	10	uA
I _{GSS}	Gate to Source Leakage Current	V _{GS} =V _{GSS} , V _{DS} =0V	-	-	±100	nA

D-S Diode Characteristics and Maximum Rating @T_C=25 °C unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I _S	Maximum Drain to Source Diode Forward Current		-	-	4	A
V _{SD}	Drain-Source Diode Forward Voltage	V _{GS} =0V, I _S =4A	-	1.0	1.3	V
t _{rr}	Reverse Recovery Time	V _{GS} =0V, I _S =4A,	-	650	-	ns
Q _{rr}	Reverse Recovery Charge	di/dt=-100A/us	-	6.5	-	nC

Switching Characteristics @T_C=25 °C unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
t _{d(on)}	Turn-on Delay Time	I _D =4A , V _{DD} =450V, R _G =25Ω (Note 3)	-	27	58	ns
t _r	Turn-on Rise Time		-	46	95	ns
t _{d(off)}	Turn-off Delay Time		-	40	82	ns
t _f	Turn-off Fall Time		-	33	75	ns
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =25V, f=1.0MHz	-	975	1100	pF
C _{oss}	Output Capacitance		-	86	105	pF
C _{rss}	Reverse Transfer Capacitance		-	2.3	4.5	pF
Q _g	Total Gate Charge	I _D =4A, V _{DD} =720V V _{GS} =10V (Note 3)	-	17	22	nC
Q _{gs}	Gate to Emitter Charge		-	4.5	-	nC
Q _{gd}	Gate to Collector Charge		-	7.0	-	nC

Note:

1. Repetitive rating: pulse-width limited by maximum junction temperature
2. L=67mH, I_D=4A, V_G=10V, V_{DD}=50V
3. Essentially independent of operating temperature typical characteristics

Typical Performance Characteristics

Fig. 1. Typical on-Resistance Characteristics




Fig. 2. Typical Transfer Characteristics




Fig. 3. Static on-Resistance vs. I_D




Fig. 4. Body Diode Forward Voltage vs. I_{DR}




Fig. 5. Capacitance Characteristics





Fig. 6. Gate Charge Characteristics



Typical Performance Characteristics

Fig. 7. Breakdown Voltage vs. Temperature




Fig. 8. Static on-Resistance vs. Temperature




Fig. 9. Maximum Safe Operating Area-SQP4N90




Fig. 10. Maximum Safe Operating Area-SQPF4N90






Fig. 11. Maximum Drain Current vs. Temperature



Package Dimensions

TO-220

(Dimensions in Millimeters)



Package Dimensions

TO-220F

(Dimensions in Millimeters)

