

SQA23N50

500V 23A N-channel Enhancement Mode Power MOSFET

Features

- Low on-Resistance: $R_{DS(on)}=0.203\ \Omega$ (typ.)
- Special Process Technology for high ESD Capability
- 100% Avalanche Test
- Good Stability and Uniformity with High E_{AS}



Description

The SQA23N50 is an N-Channel enhancement mode power MOSFET, it has low static on-resistance and high avalanche energy strength. This device provide excellent switching performance for UPS,DC-DC converters and AC-DC power supply.

Applications

- UPS Applications
- DC-DC Converters and AC-DC Power Supply

Package Type & Internal Circuit



Absolute Maximum Ratings @ $T_c=25\ ^\circ\text{C}$ unless otherwise noted

Symbol	Parameter		Ratings	Unit
V_{DSS}	Drain to Source Voltage		500	V
V_{GSS}	Gate to Source Voltage		± 30	V
I_D	Drain Current	$T_c=25^\circ\text{C}$	23	A
		$T_c=100^\circ\text{C}$	15	A
I_{DM}	Pulsed Drain Current	(Note1)	92	A
P_D	Maximum Power Dissipation	$T_c=25^\circ\text{C}$	284	W
	Derate above 25°C		2.27	W/ $^\circ\text{C}$
E_{AS}	Single Pulsed Avalanche Energy	(Note 2)	1562	mJ
T_J	Operating Junction Temperature Range		-55~+150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range		-55~+150	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Ratings	Unit
$R_{th(J-C)}$	Thermal Resistance, Junction to case	0.44	$^\circ\text{C/W}$
$R_{th(J-A)}$	Thermal Resistance, Junction to Ambient	40	$^\circ\text{C/W}$

Electrical Characteristics @T_C=25 °C unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV _{DSS}	Drain to Source Breakdown Voltage	V _{GS} =0V, I _D =250uA	500	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250uA	2.0	3.35	4.0	V
R _{DS(on)}	Static Drain-Source On-Resistance	V _{GS} =10V, I _D =11.5A	-	0.203	0.245	Ω
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =V _{DSS} , V _{GS} =0V	-	-	1	uA
I _{GSS}	Gate to Source Leakage Current	V _{GS} =V _{GSS} , V _{DS} =0V	-	-	±100	nA

D-S Diode Characteristics and Maximum Rating @T_C=25 °C unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I _S	Maximum Drain to Source Diode Forward Current		-	-	23	A
V _{SD}	Drain-Source Diode Forward Voltage	V _{GS} =0V, I _S =23A	-	0.884	1.35	V
T _{rr}	Reverse Recovery Time	V _{GS} =0V, I _S =23A,	-	0.5	-	us
Q _{rr}	Reverse Recovery Charge	di/dt=-100A/us	-	8	-	uC

Switching Characteristics @T_C=25 °C unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
t _{d(on)}	Turn-on Delay Time	I _D =23A, V _{DD} =250V, R _G =25 Ω (Note 3)	-	95	-	ns
t _r	Turn-on Rise Time		-	380	-	ns
t _{d(off)}	Turn-off Delay Time		-	95	-	ns
t _f	Turn-off Fall Time		-	95	-	ns
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =25V, f=1.0MHz	-	2565	-	pF
C _{oss}	Output Capacitance		-	380	-	pF
C _{rss}	Reverse Transfer Capacitance		-	38	-	pF
Q _g	Total Gate Charge	I _D =23A, V _{DS} =400V V _{GS} =10V (Note 3)	-	66.5	-	nC
Q _{gs}	Gate to Emitter Charge		-	17.1	-	nC
Q _{gd}	Gate to Collector Charge		-	33.3	-	nC

Note:

1. Repetitive rating: pulse-width limited by maximum junction temperature
2. L=5mH, I_{AS}=25A, V_{DD}=50V, V_G=10V, @T_C=25°C
3. Essentially independent of operating temperature typical characteristics

Typical Performance Characteristics

Fig. 1. Typical on-Resistance Characteristics




Fig. 3. Static on-Resistance vs. I_D




Fig. 5. Capacitance Characteristics




Fig. 2. Typical Transfer Characteristics




Fig. 4. Body Diode Forward Voltage vs. I_{DR}





Fig. 6. Gate Charge Characteristics



Typical Performance Characteristics

Fig. 7. Breakdown Voltage vs. Temperature




Fig. 8. Static on-Resistance vs. Temperature




Fig. 9. Maximum Safe Operating Area




Fig. 10. Maximum Drain Current vs. Temperature





Fig. 11. Transient Thermal Response Curve



Package Dimensions

TO-3PN

(Dimensions in Millimeters)

